

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**Trade name: **SPRAY 600 PAINT REMOVER**

Article number: B494

UFI: U770-S07R-N007-D2Q3

1.2 Relevant identified uses of the substance or mixture and uses advised against**Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

Environmental release category ERC2 Formulation into mixture

Article category AC1 Vehicles

Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

Trade name: SPRAY 600 PAINT REMOVER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:
dimethoxymethane

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.

vPvB: Not applicable.

Trade name: SPRAY 600 PAINT REMOVER**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures**

Description: Mixture of hazardous substances listed below with nonhazardous additions.

Dangerous components:

CAS: 646-06-0	1,3-dioxolane	40-<45%
EINECS: 211-463-5	 Flam. Liq. 2, H225	
Index number: 605-017-00-2		
RTECS: JH 6760000		
CAS: 115-10-6	dimethyl ether	35-<40%
EINECS: 204-065-8	 Flam. Gas 1A, H220	
Index number: 603-019-00-8	 Acute Tox. 2, H330	
RTECS: PM 4780000	Press. Gas (Comp.), H280	
CAS: 109-87-5	dimethoxymethane	15-<20%
EINECS: 203-714-2	 Flam. Liq. 2, H225	
RTECS: PA 8750000	 Skin Sens. 1, H317	
CAS: 108-01-0	2-dimethylaminoethanol	1-<5%
EINECS: 203-542-8	 Flam. Liq. 3, H226	
Index number: 603-047-00-0	 Skin Corr. 1B, H314	
RTECS: KK 6125000	 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
	Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	1-<5%
EINECS: 265-149-8	 Flam. Liq. 3, H226	
Index number: 649-422-00-2	 Asp. Tox. 1, H304	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters**

Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards

Special protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by

Continue on page 4

GB

Trade name: SPRAY 600 PAINT REMOVER

firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm

Long-term value: 766 mg/m³, 400 ppm

109-87-5 dimethoxymethane

WEL Short-term value: 3950 mg/m³, 1250 ppm

Long-term value: 3160 mg/m³, 1000 ppm

108-01-0 2-dimethylaminoethanol

WEL Short-term value: 22 mg/m³, 6 ppm

Long-term value: 7.4 mg/m³, 2 ppm

8002-74-2 Paraffin waxes and Hydrocarbon waxes

WEL Short-term value: 6 mg/m³

Long-term value: 2 mg/m³

Regulatory information WEL: EH40/2020

Additional information: The lists valid during the making were used as basis.

Continue on page 5
GB

Trade name: SPRAY 600 PAINT REMOVER

8.2 Exposure controls

- Personal protective equipment:
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- Respiratory protection:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

- Eye protection:
Safety glasses



Tightly sealed goggles

- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Gaseous
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Mixture is non-soluble (in water).

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-24.9 °C (115-10-6 dimethyl ether)

Trade name: SPRAY 600 PAINT REMOVER

· Flash point:	< 0 °C
· Flammability	Not applicable.
· Autoignition temperature:	235 °C
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	20.5 Vol %
· Vapour pressure at 20 °C:	5,200 hPa
· Density at 20 °C:	0.857 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	0 mm ² /s
· Solvent content:	
Organic solvents:	35.8 %
VOC (EC)	306.4 g/l
Solids content (volume):	64.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 102,622 mg/kg (rat)
Dermal LD50 70,296 mg/kg (rabbit)
Inhalative LC50/4 h 167 mg/l

646-06-0 1,3-dioxolane

Oral LD50 3,000 mg/kg (rat)
Dermal LD50 8,480 mg/kg (rabbit)

Continue on page 7
GB

Trade name: SPRAY 600 PAINT REMOVER

Inhalative LC50/4 h 20,650 mg/l (rat)

115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

109-87-5 dimethoxymethane

Oral LD50 5,708 mg/kg (rabbit)

108-01-0 2-dimethylaminoethanol

Oral LD50 2,000 mg/kg (rat)

Dermal LD50 1,370 mg/kg (rabbit)

Inhalative LC50/4 h 3.25 mg/l (mouse)

- Primary irritant effect:
- Skin corrosion/irritation
Causes skin irritation.
- Serious eye damage/irritation
Causes serious eye irritation.
- Respiratory or skin sensitisation
May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

HP3 Flammable

Trade name: SPRAY 600 PAINT REMOVER

HP13 Sensitising

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

*

SECTION 14: Transport information

· **14.1 UN-Number**

· ADR, IMDG, IATA

UN1950

· **14.2 UN proper shipping name**

· ADR

UN1950 AEROSOLS

· IMDG

AEROSOLS

· IATA

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· ADR



· Class

2.5F Gases.

· Label

2.1

· IMDG, IATA



· Class

2.1 Gases.

· Label

2.1

· **14.4 Packing group**

· ADR, IMDG, IATA

Void

· **14.5 Environmental hazards:**

· Marine pollutant:

No

· **14.6 Special precautions for user**

Warning: Gases.

· Hazard identification number (Kemler code):

-

· EMS Number:

F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear of
living quarters.

· Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1
except for division 1.4.

For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II
of Marpol and the IBC Code**

Not applicable.

Continue on page 9
GB

Trade name: SPRAY 600 PAINT REMOVER

- Transport/Additional information:
 - ADR
 - Limited quantities (LQ) 1L
 - Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
 - Transport category 2
 - Tunnel restriction code D
 - IMDG
 - Limited quantities (LQ) 1L
 - Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
 - UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- None of the ingredients is listed.
- Poisons Act
- Regulated explosives precursors
- None of the ingredients is listed.
- Regulated poisons
- None of the ingredients is listed.
- Reportable explosives precursors
- None of the ingredients is listed.
- Reportable poisons
- None of the ingredients is listed.
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02 GHS07

- Signal word Danger
- Hazard-determining components of labelling:
dimethoxymethane
- Hazard statements
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- Precautionary statements
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Continue on page 10
GB

Trade name: SPRAY 600 PAINT REMOVER

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.
- REGULATION (EU) 2019/1148
- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.
- Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.
- Regulation (EC) No 273/2004 on drug precursors
None of the ingredients is listed.
- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
- Classification according to Regulation (EC) No 1272/2008
Aerosols, Section 2.3.1 Bridging principles
Skin corrosion/irritation The classification of the mixture is generally based on the calculation method using
Serious eye damage/irritation substance data according to Regulation (EC) No 1272/2008.
Skin sensitisation
- Contact:
HB BODY S.A
Regulatory Officer
Ms Athina Kapourani
Ph: +30 2310 790000
email: a.kapourani@hbbody.com
- * Data compared to the previous version altered.

Trade name: SPRAY 600 PAINT REMOVER

Annex: Exposure scenario

Short title of the exposure scenario

Sector of Use

SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

Article category AC1 Vehicles

Environmental release category ERC2 Formulation into mixture

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Aerosol

Concentration of the substance in the mixture The substance is main component.

Used amount per time or activity Smaller than 100 g per application.

Other operational conditions

Other operational conditions affecting environmental exposure No special measures required.

Other operational conditions affecting worker exposure

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with eyes.

Other operational conditions affecting consumer exposure Keep out of the reach of children.

Other operational conditions affecting consumer exposure during the use of the product

Not applicable.

Risk management measures

Worker protection

Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Avoid contact with the eyes.

Tightly sealed goggles

Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Observe consumer information and advice on safe use.

Trade name: SPRAY 600 PAINT REMOVER· **Environmental protection measures**· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.

· **Soil** The product is only processed over the concrete collecting basin.· **Disposal measures** Ensure that waste is collected and contained.· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging· **Exposure estimation**· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

The highest inhalative exposure to be expected for consumers is 5 ppm.

The highest dermal exposure to be expected for consumers is 5 mg / kg / day.

The highest oral exposure to be expected for consumers is 0.5 mg / kg / day.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.