

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**Trade name: **SPRAY P311 ZINC WELDING PRIMER**

Article number: B210

UFI: 1190-D0R3-200M-97XF

1.2 Relevant identified uses of the substance or mixture and uses advised against**Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay

Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Environmental release category ERC2 Formulation into mixture

Article category AC1 Vehicles

Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

Trade name: SPRAY P311 ZINC WELDING PRIMER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Eye Irrit. 2

H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

GHS07

GHS09

Signal word Danger

Hazard-determining components of labelling:
butanone

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.

Trade name: **SPRAY P311 ZINC WELDING PRIMER**

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· Description: Mixture of hazardous substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 106-97-8	butane, pure	25-<30%
EINECS: 203-448-7	 Flam. Gas 1A, H220	
Index number: 601-004-00-0	 Acute Tox. 3, H331	
RTECS: EJ 4200000	Press. Gas (Comp.), H280	
	Note: C	
CAS: 78-93-3	butanone	20-<25%
EINECS: 201-159-0	 Flam. Liq. 2, H225	
Index number: 606-002-00-3	 Eye Irrit. 2, H319; STOT SE 3, H336	
RTECS: EL 6475000		
Reg.nr.: 01-2119457290-43-0000		
CAS: 7440-66-6	zinc powder -zinc dust (stabilized)	15-<20%
EINECS: 231-175-3	 Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1)	
Index number: 030-001-01-9		
CAS: 1330-20-7	xylene	5-<10%
Index number: 601-022-00-9	 Flam. Liq. 3, H226	
	 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 75-28-5	isobutane	1-<5%
EINECS: 200-857-2	 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
RTECS: TZ 4300000	Note: C	
CAS: 74-98-6	propane	1-<5%
EINECS: 200-827-9	 Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas (Comp.), H280	
RTECS: TX 2275000		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Generally the product does not irritate the skin.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

· After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture No further relevant information available.

Continue on page 4

GB

Trade name: SPRAY P311 ZINC WELDING PRIMER**5.3 Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards**Speial protective equipment and fire fighting procedures:**

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.**Further information about storage conditions:** Keep container tightly sealed.**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****106-97-8 butane, pure**

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

Trade name: SPRAY P311 ZINC WELDING PRIMER

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

1333-86-4 Carbon black

WEL Short-term value: 7 mg/m³
Long-term value: 3.5 mg/m³

- Regulatory information WEL: EH40/2020
- Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L
Medium: urine
Sampling time: post shift
Parameter: butan-2-one

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

- Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

Continue on page 6
GB

Trade name: SPRAY P311 ZINC WELDING PRIMER

- Eye protection:
Safety glasses



Tightly sealed goggles

- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol
Colour: According to product specification

· Odour: Characteristic

· Odour threshold: Not determined.

· pH-value: Mixture is non-soluble (in water).

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: -44.5 °C

· Flash point: < 0 °C

· Flammability: Not applicable.

· Autoignition temperature: 365 °C

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

Lower: 1.5 Vol %

Upper: 11.5 Vol %

· Vapour pressure at 20 °C: 2,100 hPa

· Density: Not determined.

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not applicable.

· Solubility in / Miscibility with
water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· Solvent content:

Organic solvents: 56.5 %

VOC (EC) 597.4 g/l

Solids content (volume): 40.3 %

9.2 Other information

No further relevant information available.

Trade name: SPRAY P311 ZINC WELDING PRIMER

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - Acute toxicity Based on available data, the classification criteria are not met.
 - LD/LC50 values relevant for classification:
-
- ATE (Acute Toxicity Estimates)**
Dermal LD50 28.515 mg/kg (rabbit)
Inhalative LC50/4 h 157 mg/l
- 106-97-8 butane, pure**
Inhalative LC50/4 h 658 mg/l (rat)
- 78-93-3 butanone**
Oral LD50 3,300 mg/kg (rat)
Dermal LD50 5,000 mg/kg (rabbit)
- 1330-20-7 xylene**
Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)
- Primary irritant effect:
 - Skin corrosion/irritation Based on available data, the classification criteria are not met.
 - Serious eye damage/irritation
Causes serious eye irritation.
 - Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
 - Additional toxicological information:
 - CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
 - Germ cell mutagenicity Based on available data, the classification criteria are not met.
 - Carcinogenicity Based on available data, the classification criteria are not met.
 - Reproductive toxicity Based on available data, the classification criteria are not met.
 - STOT-single exposure
May cause drowsiness or dizziness.
 - STOT-repeated exposure Based on available data, the classification criteria are not met.
 - Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
 - Aquatic toxicity:
This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea
- **12.2 Persistence and degradability**
This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
- **12.3 Bioaccumulative potential** No further relevant information available.

Trade name: SPRAY P311 ZINC WELDING PRIMER

- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- Remark: Toxic for fish
- Additional ecological information:
- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Other adverse effects** No further relevant information available.

*

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- European waste catalogue

 - HP3 Flammable
 - HP4 Irritant - skin irritation and eye damage
 - HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
 - HP14 Ecotoxic
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

*

SECTION 14: Transport information

- **14.1 UN-Number**
- ADR, IMDG, IATA UN1950
- **14.2 UN proper shipping name**
- ADR UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
- IMDG AEROSOLS, MARINE POLLUTANT
- IATA AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- ADR
- 
- Class 2 5F Gases.
- Label 2.1
- IMDG
- 
- Class 2.1 Gases.

Continue on page 9
GB

Trade name: SPRAY P311 ZINC WELDING PRIMER

· Label	2.1
· IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

Trade name: SPRAY P311 ZINC WELDING PRIMER

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:
butanone

· Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

78-93-3 butanone: 3

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 butanone: 3

Trade name: SPRAY P311 ZINC WELDING PRIMER

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

*

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
- **Classification according to Regulation (EC) No 1272/2008**

Aerosols, Section 2.3.1	Bridging principles
Serious eye damage/irritation	The classification of the mixture is generally based on the
Specific target organ toxicity (single exposure)	calculation method using substance data according to
Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	Regulation (EC) No 1272/2008.

- **Department issuing SDS:** Department of Quality Control
- **Contact:**
HB BODY S.A
Regulatory Officer
Ms Athina Kapourani
Ph: +30 2310 790000
email: a.kapourani@hbbody.com
- * Data compared to the previous version altered.

GB
Continue on page 12

Trade name: SPRAY P311 ZINC WELDING PRIMER

Annex: Exposure scenario 1

Short title of the exposure scenario

Sector of Use

- SU21 Consumer uses: Private households / general public / consumers
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay

Process category

- PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Article category AC1 Vehicles

Environmental release category ERC2 Formulation into mixture

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Aerosol

Concentration of the substance in the mixture The substance is main component.

Used amount per time or activity Smaller than 100 g per application.

Other operational conditions

Other operational conditions affecting environmental exposure Use only on hard ground.

Other operational conditions affecting worker exposure

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Keep container dry.

Avoid contact with the skin.

Other operational conditions affecting consumer exposure

No special measures required.

Keep out of the reach of children.

Other operational conditions affecting consumer exposure during the use of the product
Not applicable.

Risk management measures

Worker protection

Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Store in cool, dry place in tightly closed receptacles.

Ensure that suitable extractors are available on processing machines

Do not dilute with water.

Personal protective measures

Avoid contact with the eyes.

Tightly sealed goggles

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Continue on page 13

GB

Trade name: SPRAY P311 ZINC WELDING PRIMER· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Keep locked up and out of the reach of children.

· **Environmental protection measures**· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· **Soil**

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging· **Exposure estimation**· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

The highest inhalative exposure to be expected for consumers is 50 ppm.

The highest dermal exposure to be expected for consumers is 1 mg / kg / day.

The highest oral exposure to be expected for consumers is 1 mg / kg / day.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB

Continue on page 14

Trade name: SPRAY P311 ZINC WELDING PRIMER

Annex: Exposure scenario 2

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture Raw material.

Other operational conditions

Other operational conditions affecting environmental exposure No special measures required.

Other operational conditions affecting worker exposure

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Other operational conditions affecting consumer exposure No special measures required.

Other operational conditions affecting consumer exposure during the use of the product

Not applicable.

Risk management measures

Worker protection

Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed goggles

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures

Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil The product is only processed over the concrete collecting basin.

Disposal measures Ensure that waste is collected and contained.

Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

Exposure estimation

Consumer

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.