

Page 1/14

Printing date: 01.04.2025 Revision date: 01.04.2025

Version no. 15

Safety data sheet according to UK REACH

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SPRAY P960 WASH PRIMER

· Article number: B604

· UFI: 4TR0-F0FC-R00Q-2Y5J

1.2 Relevant identified uses of the substance or mixture and uses advised against

- · Life cycle stages IS Use at industrial Sites
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU17 General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- Product category PC9a Coatings and paints, thinners, paint removers
- Process category

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

- · Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article
- · Article category AC1 Vehicles
- Technical function Other
- · Application of the substance / the mixture Surface protection

1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE Ph: +30 2310 790 000

Fax: +30 2310 790 033 www.hbbody.com

email: hbbody@hbbody.com

· Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE Ph: +30 2310 790 000 Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

Page 2/14

Printing date: 01.04.2025

Revision date: 01.04.2025

Version no. 15

Trade name: SPRAY P960 WASH PRIMER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

STOT SE 3

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

02 GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

butan-1-ol

butanone

propan-2-ol

n-butvl ester

· Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH208 Contains amines, polyethylenepoly-HEPA. May produce an allergic reaction.

Buildup of explosive mixtures possible without sufficient ventilation.

Continue on page 3

Safety data sheet

according to UK REACH

Page 3/14 Safety data sheet
Printing date: 01.04.2025 according to UK REACH

Revision date: 01.04.2025

Version no. 15

Trade name: SPRAY P960 WASH PRIMER

2.3 Other hazards

Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· Description: Mixture of hazardous substances listed below with nonhazardous additions.

٦	าล	ทต	ero	LIS	com	no	ner	ıts:
- 1	10	1111	C1 ()	11.5			1161	11.5

Dangerous components.		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 RTECS: PM 4780000	dimethyl ether Flam. Gas 1A, H220 Acute Tox. 2, H330 Press. Gas (Comp.), H280	45-<50%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 RTECS: EL 6475000 Reg.nr.: 01-2119457290-43-0000	butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	25-<30%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 RTECS: NT 8050000 Reg.nr.: 01-2119457558-25-0002 01-2119457558-25-0001	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 RTECS: AF 7350000 Reg.nr.: 01-2119485493-29-007 01-2119485493-29-003 01-2119485493-29-005 01-2119485493-29	n-butyl ester Flam. Liq. 3, H226 STOT SE 3, H336	5-<10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 RTECS: EO 1400000 Reg.nr.: 01-2119484630-38-0000	butan-1-ol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335 STOT SE 3, H336	≥3-<5%
CAS: 34590-94-8 EINECS: 252-104-2 RTECS: JM 1575000	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	≥0-<5%
CAS: 68131-73-7 EINECS: 268-626-9 Index number: 612-121-00-1	amines, polyethylenepoly-HEPA Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1) Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≥0.25-<0.9%
A shalled a self-time for many actions of the con-	· ·	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

Page 4/14 Safety data sheet
Printing date: 01.04.2025 according to UK REACH

Version no. 15

Trade name: SPRAY P960 WASH PRIMER

· After skin contact:

Revision date: 01.04.2025

In case of skin contact DO NOT clean effected area with solvents or thinners. Take off all contaminated clothing at once. Wash skin thoroughly with neutral pH soap and water. In any suspicion that skin irritation persists call a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards

Speial protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Page 5/14 Safety data sheet
Printing date: 01.04.2025 according to UK REACH

Revision date: 01.04.2025

Version no. 15

Trade name: SPRAY P960 WASH PRIMER

7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:
 - Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

123-86-4 n-butyl ester

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm

Sk

Regulatory information WEL: EH40/2020 Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L Medium: urine

Sampling time: post shift Parameter: butan-2-one

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Page 6/14
Printing date: 01.04.2025

Revision date: 01.04.2025

Version no. 15

Trade name: SPRAY P960 WASH PRIMER

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the baseis of the different substances in the preparation.

- · For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

· Eye protection: Safety glasses



Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Appearance:

Form: Aerosol
Colour: Grey
Odour: Characteristic

· Odour threshold: Not determined.

· pH-value: Mixture is non-soluble (in water).

Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: -24.9 °C (115-10-6 dimethyl ether)

· Flash point: < 0 °C

· Flammability Not applicable.

· Autoignition temperature: 235 °C

Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

Lower: 1.8 Vol %

Continue on page 7

Safety data sheet

according to UK REACH

Page 7/14 Safety data sheet
Printing date: 01.04.2025 according to UK REACH

Revision date: 01.04.2025 Version no. 15

Trade name: SPRAY P960 WASH PRIMER

Upper: 18.6 Vol %

· Vapour pressure at 20 °C: 5,200 hPa

· Density at 20 °C: 0.814 g/cm³

· Relative density Not determined.

· Vapour density Not determined.

· Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic at 20 °C: 0 mm²/s

· Solvent content:

Organic solvents: 91.3-<92.3 % VOC (EC) 743.3-<751.2 g/l >7.7-8.7 %

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 17,421 mg/kg (rat)

115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

78-93-3 butanone

Oral LD50 3,300 mg/kg (rat)
Dermal LD50 5,000 mg/kg (rabbit)

67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat)
Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

123-86-4 n-butyl ester

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)

Inhalative LC50/4 h >21 mg/l (rat)

Page 8/14 Safety data sheet
Printing date: 01.04.2025 according to UK REACH

Revision date: 01.04.2025

Version no. 15

Trade name: SPRAY P960 WASH PRIMER

71-36-3 butan-1-ol

Oral LD50 790 mg/kg (rat)
Dermal LD50 3,400 mg/kg (rabbit)
Inhalative LC50/4 h 8,000 mg/l (rat)

34590-94-8 Dipropylene glycol monomethyl ether

Oral LD50 5,135 mg/kg (rat)
Dermal LD50 >19,000 mg/kg (rab)
68131-73-7 amines, polyethylenepoly-HEPA

Oral LD50 500 mg/kg (ATE)
Dermal LD50 1,100 mg/kg (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye damage.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

· Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

Page 9/14 Safety data sheet Printing date: 01.04.2025 according to UK REACH

Version no. 15

Revision date: 01.04.2025

Trade name: SPRAY P960 WASH PRIMER

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

HP3 Flammable

HP4 Irritant - skin irritation and eye damage

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP14 Ecotoxic

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number

· ADR, IMDG, IATA UN1950

14.2 UN proper shipping name

·ADR **UN1950 AEROSOLS**

·IMDG **AEROSOLS**

·IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases. · Label 2.1

14.4 Packing group

· ADR, IMDG, IATA Void

14.5 Environmental hazards:

14.6 Special precautions for user

· Hazard identification number (Kemler code):

· EMS Number:

· Stowage Code

Not applicable.

Warning: Gases.

F-D.S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of

living quarters.

Page 10/14

Printing date: 01.04.2025 Revision date: 01.04.2025

Version no. 15

Trade name: SPRAY P960 WASH PRIMER

 Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1

Safety data sheet

according to UK REACH

except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

 Transport category Tunnel restriction code D

·IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· Poisons Act

· Regulated explosives precursors

7664-38-2 phosphoric acid: 30%

· Regulated poisons

108-95-2 phenol: Listed

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

108-95-2 phenol: Listed

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02





· Signal word Danger

Hazard-determining components of labelling:

butan-1-ol

butanone

propan-2-ol

n-butyl ester

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Page 11/14

Printing date: 01.04.2025

Safety data sheet according to UK REACH

Revision date: 01.04.2025 Version no. 15

Trade name: SPRAY P960 WASH PRIMER

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

78-93-3 butanone: 3 108-88-3 toluene: 3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 butanone: 3 108-88-3 toluene: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

Page 12/14 Printing date: 01.04.2025 Revision date: 01.04.2025

Version no. 15

Safety data sheet according to UK REACH

Trade name: SPRAY P960 WASH PRIMER

H410 Very toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1

Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

· Contact: HB BODY S.A Regulatory Officer Ms Athina Kapourani Ph: +30 2310 790000

email: a.kapourani@hbbody.com

* Data compared to the previous version altered.

Bridging principles

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

GB e 13

Page 13/14

Printing date: 01.04.2025

Safety data sheet according to UK REACH

Version no. 15

Trade name: SPRAY P960 WASH PRIMER

Annex: Exposure scenario

Short title of the exposure scenario

Sector of Use

Revision date: 01.04.2025

SU21 Consumer uses: Private households / general public / consumers

SU17 General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

· Article category AC1 Vehicles

· Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

Technical function Other

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- * Conditions of use According to directions for use.
- Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Aerosol
- · Concentration of the substance in the mixture The substance is main component.
- · Used amount per time or activity Smaller than 100 g per application.

Other operational conditions

Other operational conditions affecting environmental exposure

No special measures required.

Use only on hard ground.

Other operational conditions affecting worker exposure

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

- Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

- · Worker protection
- Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

Personal protective measures

Avoid contact with the eyes.

Tightly sealed goggles

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Page 14/14

Printing date: 01.04.2025

Safety data sheet according to UK REACH

Revision date: 01.04.2025 Version no. 15

Trade name: SPRAY P960 WASH PRIMER

Observe consumer information and advice on safe use.

- · Environmental protection measures
- · Water

Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required. Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· Soil

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

- Disposal measures Ensure that waste is collected and contained.
- Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging

Exposure estimation

· Consumer

This product is to be used by professional technitians only.

Not relevant for this Exposure Scenario.

The highest inhalative exposure to be expected for consumers is 500 ppm.

The highest dermal exposure to be expected for consumers is 5 mg / kg / day.

The highest oral exposure to be expected for consumers is 0.5 mg / kg / day.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB